



SAFETY DATA SHEET

BLAST OFF (BULK)

Page 1

Issued: 30/10/2006

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: BLAST OFF (BULK)

Use / description of product: Carburettor and choke cleaner.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: 4-HYDROXY-4-METHYLPENTAN-2-ONE 10-30%

EINECS: 204-626-7 CAS: 123-42-2

[Xi] R36

- XYLENE 30-50%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- ACETONE 30-50%

EINECS: 200-662-2 CAS: 67-64-1

[F] R11; [Xi] R36; [-] R66; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin.

Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash skin thoroughly with water and remove contaminated clothing. Obtain medical attention if symptoms develop.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET

BLAST OFF (BULK)

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Wash away spillage residues to foul sewer.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: 4-HYDROXY-4-METHYLPENTAN-2-ONE

WEL (8 hr exposure limit): 241 mg/m³ WEL (15 min exposure limit): 362 mg/m³

- XYLENE

WEL (8 hr exposure limit): 220 mg/m³ WEL (15 min exposure limit): 441 mg/m³ (Sk)

- ACETONE

WEL (8 hr exposure limit): 1210 mg/m³ WEL (15 min exposure limit): 3620 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

SAFETY DATA SHEET

BLAST OFF (BULK)

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Impermeable gloves. (Sk) noted above means can be absorbed through skin.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Red

Odour: Ketone/hydrocarbon.

Solubility in water: Slightly soluble

Boiling point/range°C: 56-157

Flammability limits %: lower: 1.1

upper: 13.0

Flash point°C: -18

Autoflammability°C: 500

Relative density: 0.84

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: 4-HYDROXY-4-METHYLPENTAN-2-ONE

IVN RAT LDLO 3024 mg/kg

ORL MUS LD50 3950 mg/kg

ORL RAT LD50 2520 mg/kg

- XYLENE

ORL MUS LD50 2119 mg/kg

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

- ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

SAFETY DATA SHEET

BLAST OFF (BULK)

12. ECOLOGICAL INFORMATION**Mobility:** Volatile.**Persistence and degradability:** Biodegradable.**Other adverse effects:** Should not be discharged directly in concentrated form to water courses.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Contact Unicorn Chemicals Ltd to arrange disposal.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1993**ADR Class:** 3**Packing group:** II**Classification code:** F1**Shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE; XYLENE)**Labelling:** 3**Hazard ID no:** 33**IMDG / IMO****UN no:** 1993**Class:** 3**Packing group:** II**EmS:** F-E,S-E***Marine pollutant:** .**Labelling:** 3**IATA / ICAO****UN no:** 1993**Class:** 3**Packing group:** II**Packing instructions:** 305(P&CA); 307(CAO)**Labelling:** 3**15. REGULATORY INFORMATION****Hazard symbols:** Highly flammable.

Harmful.

**Risk phrases:** R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

SAFETY DATA SHEET

BLAST OFF (BULK)

R36/38: Irritating to eyes and skin.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37: Wear suitable protective clothing and gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R36: Irritating to eyes.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R11: Highly flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.