



SAFETY DATA SHEET

COCOON

Page 1

Issued: 13/03/06

Revision No: 4

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: COCOON

Use / description of product: Mould protector.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN
30-50%

CAS: 64742-49-0

[F] R11; [Xn] R65; [Xi] R38; [N] R51/53; [-] R67

- XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- MINERAL OIL 1-10%

CAS: 64742-52-5

- OLEYL HYDROXYETHYL IMIDAZOLINE <1%

[Xn] R22; [C] R34; [N] R50/53

- N-OLEOYL SARCOSINE <1%

[Xi] R36/38; [N] R50/53

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE 10-30%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

[cont...]

SAFETY DATA SHEET

COCOON

4. FIRST AID MEASURES (SYMPTOMS)

- Skin contact:** There may be irritation and redness at the site of contact. Prolonged or repeated contact may defat the skin leading to dermatitis.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.
- Inhalation:** Inhalation of high levels of vapour may cause upper respiratory tract irritation. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops.
- Eye contact:** Rinse with water for 10 minutes and seek medical advice if irritation persists.
- Ingestion:** If affected, seek medical advice.
- Inhalation:** Remove to fresh air. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Alcohol resistant foam.
- Exposure hazards:** Extremely flammable. Forms explosive air-vapour mixture.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.
- Clean-up procedures:** If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid prolonged or repeated contact with skin. Smoking is forbidden.
- Storage conditions:** Store in a cool, well ventilated area, below 50°C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN
WEL (8 hr exposure limit): 1000 mg/m³
- XYLENE
WEL (8 hr exposure limit): 220 mg/m³ WEL (15 min exposure limit): 441 mg/m³ (Sk)

SAFETY DATA SHEET

COCOON

- MINERAL OIL
WEL (8 hr exposure limit): 5mg/m³ (oil mist)
- BUTANE
WEL (8 hr exposure limit): 1450 mg/m³ WEL (15 min exposure limit): 1810 mg/m³
- PROPANE
WEL (8 hr exposure limit): 1800 mg/m³ WEL (15 min exposure limit): 7200 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Use of impervious gloves is recommended. (Sk) noted above means can be absorbed through skin.

Eye protection: Wear safety glasses or goggles if risk of splashing.

Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Dark blue

Odour: Paraffinic

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.8

upper: 9.0

Flash point°C: -40

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition. Flames.

Materials to avoid: Oxidising agents.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: XYLENE
ORL MUS LD50 2119 mg/kg
ORL RAT LD50 4300 mg/kg
SCU RAT LD50 1700 mg/kg

Routes of exposure: Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.

Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Unicorn Chemicals Ltd to arrange disposal.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950

ADR Class: 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1

**IMDG / IMO**

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: .

Labelling: 2.1

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.

Irritant.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

SAFETY DATA SHEET

COCOON

environment.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S23: Do not breathe vapour/spray.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R11: Highly flammable.

R65: Harmful: may cause lung damage if swallowed.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R22: Harmful if swallowed.

R34: Causes burns.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R36/38: Irritating to eyes and skin.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.