



SAFETY DATA SHEET

CONTACT-S

Page 1

Issued: 24/02/06

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: CONTACT-S

Use / description of product: Electrical contact point/electronic equipment cleaner.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0) 70-90%

EINECS: 265-151-9 CAS: 64742-49-0

[F] R11; [N] R51/53; [Xn] R65

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE 10-30%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

Contains: No ingredients classified as hazardous.

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact. Prolonged or repeated contact may defat the skin leading to dermatitis.

Eye contact: There may be irritation and redness.

Ingestion: Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

Inhalation: Inhalation of high levels of vapour may cause upper respiratory tract irritation. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. Drowsiness or mental confusion may occur. There may be loss of consciousness. Convulsions may occur.

[cont...]

SAFETY DATA SHEET

CONTACT-S

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Wash with soap and water. Seek medical advice if irritation develops.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** If affected, seek medical advice.
- Inhalation:** Remove to fresh air. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Alcohol resistant foam.
- Exposure hazards:** Extremely flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.
- Clean-up procedures:** If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid prolonged or repeated contact with skin. Smoking is forbidden.
- Storage conditions:** Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0)
WEL (8 hr exposure limit): 1200 mg/m³
- BUTANE
WEL (8 hr exposure limit): 1450 mg/m³ WEL (15 min exposure limit): 1810 mg/m³
 - PROPANE
WEL (8 hr exposure limit): 1800 mg/m³ WEL (15 min exposure limit): 7200 mg/m³
- Engineering measures:** Ensure there is sufficient ventilation of the area. Naphtha (Petroleum), Hydrotreated Light; Low Boiling Hydrogen OEL: 1000mg/m³ (8h TWA-suggested). Butane OEL: 600ppm (8h TWA); 750ppm (15min STEL).
- Respiratory protection:** If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

SAFETY DATA SHEET

CONTACT-S

- Hand protection:** Use of impervious gloves is recommended.
Eye protection: Wear safety glasses or goggles if risk of splashing.
Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Aerosol
Colour: Colourless
Odour: Paraffinic
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Insoluble
Flammability limits %: lower: 0.8
upper: 9.0
Flash point°C: -40
Autoflammability°C: >230

10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions.
Conditions to avoid: Heat. Sources of ignition. Flames.
Materials to avoid: Oxidising agents.

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0)
ORL RAT LD50 >2000 mg/kg
Routes of exposure: Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.

12. ECOLOGICAL INFORMATION

- Mobility:** Insoluble in water.
Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

- Disposal operations:** Contact Unicorn Chemicals Ltd to arrange disposal.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

- UN no:** 1950
Classification code: 5F
ADR Class: 2

SAFETY DATA SHEET

CONTACT-S

Shipping name: AEROSOLS

Labelling: 2.1



IMDG / IMO

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: .

Labelling: 2.1

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

SAFETY DATA SHEET
CONTACT-S

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R11: Highly flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.