



SAFETY DATA SHEET

DASHBOARD POLISH

Page 1

Issued: 23/02/06

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: DASHBOARD POLISH

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED HEAVY 50-70%

CAS: 64742-48-9

[-] R10; [Xn] R65; [-] R66

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

[cont...]

SAFETY DATA SHEET
DASHBOARD POLISH

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED HEAVY
WEL (8 hr exposure limit): 1000mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Requirement for respiratory protection is unlikely.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Off-white

Odour: Hydrocarbon.

Oxidising: Non-oxidising (by EC criteria)

Viscosity: Viscous

Boiling point/range°C: 150-200

Flammability limits %: lower: 0.6

upper: 8.0

Flash point°C: 44

SAFETY DATA SHEET

DASHBOARD POLISH

Autoflammability°C: 240**Relative density:** 0.8**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions. Stable at room temperature.**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED HEAVY
ORL RAT LD50 >5000 mg/kg**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Contact Unicorn Chemicals Ltd to arrange disposal.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1993**ADR Class:** 3**Packing group:** III**Classification code:** F1**Shipping name:** FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY)**Labelling:** 3**Hazard ID no:** 33**IMDG / IMO****UN no:** 1993**Class:** 3**Packing group:** III**EmS:** F-E,S-E***Marine pollutant:** .**Labelling:** 3

IATA / ICAO

UN no: 1993	Class: 3
Packing group: III	Packing instructions: 309(P&CA); 310(CAO)
Labelling: 3	

15. REGULATORY INFORMATION

Risk phrases: R10: Flammable.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.
S23: Do not breathe vapour/spray.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

Risk phrases used in s.2: R10: Flammable.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.