



SAFETY DATA SHEET

JET

Page 1

Issued: 24/02/06

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: JET

Use / description of product: Brake wash/solvent degreaser.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN
30-50%

CAS: 64742-49-0

[F] R11; [Xn] R65; [Xi] R38; [N] R51/53; [-] R67

- ACETONE 10-30%

EINECS: 200-662-2 CAS: 67-64-1

[F] R11; [Xi] R36; [-] R66; [-] R67

- PROPAN-2-OL 10-30%

EINECS: 200-661-7 CAS: 67-63-0

[F] R11; [Xi] R36; [-] R67

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE 10-30%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

[cont...]

SAFETY DATA SHEET

JET

Eye contact: There may be irritation and pain. The eyes may water profusely.

Ingestion: Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

Inhalation: Inhalation of high levels of vapour may cause upper respiratory tract irritation. Drowsiness or mental confusion may occur. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: If affected, seek medical advice.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam.

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN
WEL (8 hr exposure limit): 1000 mg/m³

- ACETONE

WEL (8 hr exposure limit): 1210 mg/m³ WEL (15 min exposure limit): 3620 mg/m³

SAFETY DATA SHEET

JET

- PROPAN-2-OL
WEL (8 hr exposure limit): 999 mg/m³ WEL (15 min exposure limit): 1250 mg/m³
- BUTANE
WEL (8 hr exposure limit): 1450 mg/m³ WEL (15 min exposure limit): 1810 mg/m³
- PROPANE
WEL (8 hr exposure limit): 1800 mg/m³ WEL (15 min exposure limit): 7200 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. Naphtha (Petroleum), Hydrotreated Light; Low Boiling Hydrogen OEL: 1000mg/m³ (8h TWA-suggested).

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Colourless

Odour: Ketone/hydrocarbon.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Slightly soluble

Flammability limits %: lower: 0.8

upper: 13.0

Flash point°C: -40

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Oxidising agents.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: ACETONE
IVN RAT LD50 5500 mg/kg
ORL MUS LD50 3 gm/kg
ORL RAT LD50 5800 mg/kg

- PROPAN-2-OL
IVN RAT LD50 1088 mg/kg
ORL MUS LD50 3600 mg/kg
ORL RAT LD50 5045 mg/kg
SCU MUS LDLO 6 gm/kg

SAFETY DATA SHEET

JET

Routes of exposure: Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases. May cause eye irritation.

12. ECOLOGICAL INFORMATION

Mobility: Volatile.

Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Unicorn Chemicals Ltd to arrange disposal.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950

ADR Class: 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1

**IMDG / IMO**

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: .

Labelling: 2.1

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.

Irritant.

Dangerous for the environment.



SAFETY DATA SHEET

JET

Risk phrases: R12: Extremely flammable.
R36/38: Irritating to eyes and skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S23: Do not breathe vapour/spray.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51: Use only in well-ventilated areas.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This product belongs to Hazard Groups A and S under the HSE COSHH Essentials guidelines. (Publication HSG193).

Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R11: Highly flammable.
R65: Harmful: may cause lung damage if swallowed.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67: Vapours may cause drowsiness and dizziness.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.