



SAFETY DATA SHEET

MULTI-LUBE (AEROSOL)

Page 1

Issued: 24/02/06

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MULTI-LUBE (AEROSOL)

Use / description of product: Specialised lubrication system.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: WHITE SPIRIT 10-30%

[-] R10; [Xn] R65; [Xi] R66; [-] R67; [N] R51/53

- MINERAL OIL 1-10%

CAS: 64742-52-5

- OLEYL HYDROXYETHYL IMIDAZOLINE 1-10%

[Xn] R22; [C] R34; [N] R50/53

- N-OLEOYL SARCOSINE 1-10%

[Xi] R36/38; [N] R50/53

- NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0) 30-50%

EINECS: 265-151-9 CAS: 64742-49-0

[F] R11; [N] R51/53; [Xn] R65

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE 10-30%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

[cont...]

SAFETY DATA SHEET

MULTI-LUBE (AEROSOL)

Ingestion: Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

Inhalation: Inhalation of high levels of vapour may cause upper respiratory tract irritation.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: If affected, seek medical advice.

Inhalation: Remove to fresh air. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol resistant foam.

Exposure hazards: Extremely flammable. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: WHITE SPIRIT

TWA 100ppm

- MINERAL OIL

TWA 5mg/m³ (oil mist)

- NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0)

TWA 1200 mg/m³

- BUTANE

TWA 1450 mg/m³ STEL 1810 mg/m³

- PROPANE

TWA 1800 mg/m³ STEL 7200 mg/m³

SAFETY DATA SHEET

MULTI-LUBE (AEROSOL)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective overalls.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Gold-brown

Odour: Paraffinic

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.6

upper: 9.0

Flash point°C: -40

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-49-0)

ORL RAT LD50 >2000 mg/kg

Routes of exposure: Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.

Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Unicorn Chemicals Ltd to arrange disposal.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS
Labelling: 2.1

**IMDG / IMO**

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
Dangerous for the environment.



Risk phrases: R12: Extremely flammable.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S23: Do not breathe vapour/spray.
S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

SAFETY DATA SHEET

MULTI-LUBE (AEROSOL)

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R10: Flammable.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R22: Harmful if swallowed.

R34: Causes burns.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R36/38: Irritating to eyes and skin.

R11: Highly flammable.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.