



SAFETY DATA SHEET

UNIMAC 902

Page 1

Issued: 25/08/06

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UNIMAC 902

Use / description of product: Alkaline surfactant solution.

Company name: Unicorn Chemicals Ltd

Unicorn House

Mowbray Drive

Blackpool

Lancashire

FY3 7UN

Tel: 01253 396101

Fax: 01253 302895

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: AMINOETHYLETHANOLAMINE 10-30%

EINECS: 203-867-5 CAS: 111-41-1

[Xi] R38; [Xi] R41; [Sens.] R43

- ALKYLPHENOL ETHOXYLATE 1-10%

[Xi] R36/38

- SODIUM HYDROXIDE 1-10%

EINECS: 215-185-5 CAS: 1310-73-2

[C] R35

3. HAZARDS IDENTIFICATION

Main hazards: Causes burns. Risk of serious damage to eyes. May cause sensitisation by skin contact.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Irritation or pain may occur at the site of contact. Blistering may occur. Severe burns may occur.

Eye contact: There may be irritation and redness. The eyes may water profusely. Corneal burns may occur.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Corrosive burns may appear around the lips. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

[cont...]

SAFETY DATA SHEET

UNIMAC 902

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: The product is non-combustible; appropriate extinguishing media for surrounding area should be used in fire situations.

Exposure hazards: Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: Absorb onto sand, vermiculite etc. and transfer to a suitable container, or neutralise carefully with dilute hydrochloric acid (test with litmus paper if available) and flush away with plenty of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: AMINOETHYLETHANOLAMINE
WEL (8 hr exposure limit): 2ppm (Sk)

- SODIUM HYDROXIDE

WEL (8 hr exposure limit): - WEL (15 min exposure limit): 2 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Protective gloves. (Sk) noted above means can be absorbed through skin.

Eye protection: Safety goggles. Face-shield. Ensure eye bath is to hand.

SAFETY DATA SHEET

UNIMAC 902

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC. PVC apron covering the tops of the boots. Ensure safety shower is to hand.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Pale yellow
Odour: Slightly sweet.
Solubility in water: Soluble
Relative density: 1.1
pH: 13

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Materials to avoid: Acids. Oxidising agents. Copper. Copper alloys. Chlorinated hydrocarbons.
Haz. decomp. products: Heating produces toxic nitrous gases and nitrogen oxides can be formed.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: SODIUM HYDROXIDE
IPR MUS LD50 40 mg/kg
ORL RBT LDLO 500 mg/kg
Routes of exposure: May cause irritation of skin, eyes, nose and upper respiratory tract. May cause burns.

12. ECOLOGICAL INFORMATION

Mobility: Soluble in water.
Persistence and degradability: Partially or slowly biodegradable.
Other adverse effects: A rise in the pH of water to 10.5 or above may be fatal to fish and other aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Unicorn Chemicals Ltd to arrange disposal.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1760 **ADR Class:** 8
Packing group: III **Classification code:** C9
Shipping name: CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE)
Labelling: 8 **Hazard ID no:** 80



SAFETY DATA SHEET

UNIMAC 902

IMDG / IMO

UN no: 1760	Class: 8
Packing group: III	EmS: F-A,S-B
Marine pollutant: .	Labelling: 8

IATA / ICAO

UN no: 1760	Class: 8
Packing group: III	Packing instructions: 818(P&CA); 820(CAO)
Labelling: 8	

15. REGULATORY INFORMATION**Hazard symbols:** Corrosive.

Risk phrases: R34: Causes burns.
 R41: Risk of serious damage to eyes.
 R43: May cause sensitisation by skin contact.

Safety phrases: S1/2: Keep locked up and out of the reach of children.
 S24/25: Avoid contact with skin and eyes.
 S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
 S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This product belongs to Hazard Groups C and S under the HSE COSHH Essentials guidelines (Publication HSG193).

Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R38: Irritating to skin.
 R41: Risk of serious damage to eyes.
 R43: May cause sensitisation by skin contact.
 R36/38: Irritating to eyes and skin.
 R35: Causes severe burns.

SAFETY DATA SHEET

UNIMAC 902

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.